

Evaluation, Validation and Transition of the 1/12° Global HYCOM/NCODA/PIPS System

Joe Metzger ⁽¹⁾, Harley Hurlburt ⁽¹⁾, Alan Wallcraft ⁽¹⁾, Ole
Martin Smedstad ⁽²⁾, Birol Kara ⁽¹⁾, Jay Shriver ⁽¹⁾, Lucy
Smedstad ⁽¹⁾, Pam Posey ⁽¹⁾, Prasad Thoppil ⁽³⁾ and
Debbie Franklin ⁽²⁾

(1) Naval Research Laboratory

(2) Planning Systems Inc.

(3) University of Southern Mississippi

2008 Ocean Sciences Meeting

Session 171 - U.S. GODAE: Ocean Prediction with HYCOM

5 March 2008

Report Documentation Page				Form Approved OMB No. 0704-0188	
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.					
1. REPORT DATE 05 MAR 2008		2. REPORT TYPE		3. DATES COVERED 00-00-2008 to 00-00-2008	
4. TITLE AND SUBTITLE Evaluation, Validation and Transition of the 1/12degree Global HYCOM/NCODA/PIPS System				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Naval Research Laboratory,Stennis Space Center,MS,39529				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited					
13. SUPPLEMENTARY NOTES					
14. ABSTRACT					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT Same as Report (SAR)	18. NUMBER OF PAGES 17	19a. NAME OF RESPONSIBLE PERSON
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified			

HYCOM = HYbrid Coordinate Ocean Model

NCODA = Navy Coupled Ocean Data Assimilation

PIPS = Polar Ice Prediction System

Delivery:

- Scheduled for transition to the Naval Oceanographic Office in 2008

Capability:

- Provide accurate 3D temperature, salinity and current structure
- Depict the location of mesoscale features: fronts and eddies

Progress:

- 1/12° global HYCOM/NCODA running in real-time in the NAVOCEANO operational queues since 22 Dec 2006
- Produces daily 5-day hindcast up to the nowcast time, then a 5-7 day forecast
- Graphical and digital output available through the HYCOM consortium web pages: <http://www.hycom.org>
- Validation efforts underway – comparing against operational 1/8° global NCOM (Navy Coastal Ocean Model)

Global HYCOM Configuration

- Horizontal grid: 1/12° equatorial resolution
 - 4500 x 3298 grid points, ~6.5 km spacing on average, ~3.5 km at pole
- Mercator 79°S to 47°N, then Arctic dipole patch
- Vertical coordinate surfaces: 32 for σ_2^*
- KPP mixed layer model
- Thermodynamic (energy loan) sea-ice model – switching to PIPS
- Surface forcing: **FNMOG** **NOGAPS** 0.5° wind stress, wind speed, thermal forcing, and **NOGAPS** 1.0° precipitation
- Monthly river runoff (986 rivers)
- Initialized from January climatology (GDEM3) T and S, then SSS relaxation from PHC 3.0
 - No subsurface relaxation to climatology

Validation Tasks

A. Large scale circulation features

- Determine correct placement of large scale features

B. Sea Surface Height (SSH) variability / Eddy Kinetic Energy (EKE)

- Determine if the system has a realistic level and distribution of energy at depths

C. Mixed layer depth (MLD) / sonic layer depth (SLD) / deep sound channel (DSC) / below layer gradient (BLG)

- Compare simulated vs. observed for non-assimilated buoys

D. Vertical profiles of T&S

- Quantitative comparison of simulated vs. observed for non-assimilated buoys

E. Sea surface temperature


- Evaluate whether the models are producing acceptable nowcasts and forecasts of sea surface temperature

F. Coastal sea level

- Assess the model's ability to represent observed sea surface heights

Large Scale Circulation Features


1992-2002 Mean Dynamic Ocean Topography (MDOT)



from Maximenko and Niiler (2005)

Large Scale Circulation Features


2004-2006 mean sea level from 1/12° global HYCOM/NCODA




From the 1/12° global HYCOM/NCODA hindcast simulation
standard deviation of difference (MDOT – HYCOM) = 9.2 cm
standard deviation of difference (MDOT – NCOM) = 13.0 cm

SSH Variability Evaluation

Measure of the mesoscale eddy field




Oct 92 – May 07 SSH variability based on T/P, ERS-1 and ERS-2 altimeters (from Collecte, Localisation, Satellites (CLS))




SSH variability over 2004-2006 from a 1/12° global HYCOM/NCODA hindcast simulation

SSH Variability Evaluation

Measure of the mesoscale eddy field






Oct 92 – May 07 SSH variability based on T/P, ERS-1 and ERS-2 altimeters (from Collecte, Localisation, Satellites (CLS))



SSH variability over 2004-2006 from the 1/8° global NCOM real-time simulation


Surface EKE in the Gulf Stream

Observations from
Fratantoni (2001) –
based on 1990-99
surface drifters



MLD Error Analysis

JJ/2007 MLD Median Bias Error (MdBE): model vs. ~6K assim. profiles



Temp vs. Depth Error Analysis


HYCOM/NCODA (red)

vs. NCODA analysis in z-space (green)

vs. NCODA analysis in HYCOM space (blue)

Mean error (°C)

RMSE (°C)



Based on ~5300 assimilated profiles over the period June-July 2007

Sea Surface Temperature Evaluation

Data type: **MCSST**, ~19,000,000 observations

	Mean Error		RMSE	
	HYCOM	NCOM	HYCOM	NCOM
Analysis	-.12	-.24	.55	.60
1-d fcst	-.17	-.25	.61	.63
2-d fcst	-.19	-.25	.66	.64
3-d fcst	-.21	-.26	.70	.66
4-d fcst	-.22	-	.74	-

Data type: **Drifting buoys**, ~520,000 observations

	Mean Error		RMSE	
	HYCOM	NCOM	HYCOM	NCOM
Analysis	-.08	-.25	.61	.67
1-d fcst	-.13	-.26	.73	.68
2-d fcst	-.16	-.26	.78	.69
3-d fcst	-.19	-.26	.83	.71
4-d fcst	-.21	-	.88	-

Based on thirty 4-day / 3-day forecasts from HYCOM / NCOM over the period June-July 2007; Limited between 45°S – 45°N

Sea Ice Simulation in HYCOM


- Existing public domain version of HYCOM is configured with a thermodynamic energy-loan sea ice model built in
 - First generation system
 - No ice rheology – ice grows/melts as a function of heat flux & SST
- Couple HYCOM/NCODA with a sea ice (CICE) model developed by Los Alamos
 - Next generation, advanced system
 - Additional ice physics
 - Energy-based ice ridging scheme
 - Energy-conserving thermodynamics
 - Multi-category, linearly remapped ice thickness
 - 2-way coupling between ocean and ice via the Earth System Modeling Framework (ESMF)
 - In Navy parlance: Polar Ice Prediction System (PIPS)
 - Assimilate SSM/I ice concentration in PIPS

Bering Sea HYCOM/NCODA/PIPS

Ice thickness (m) and independent NIC ice edge (black line)


No SSMI assimilation

SSMI assimilation




- HYCOM/NCODA/PIPS currently only working for regional domains
- PIPS is a clear improvement over energy-lean ice model
- SSMI ice concentration assimilation simulations produce a better fit to independent ice edge analysis

Navy Coupled Ocean Data Assimilation (NCODA)



MVOI - simultaneous analysis 5 ocean variables temperature, salinity, geopotential, layer pressure, velocity (u,v)

HYCOM/NCODA Runstream



- 1) Perform first NCODA analysis centered on tau = -126
- 2) Run HYCOM for 24 hours using incremental updating (■) over the first 6 hrs
- 3) Repeat steps 1) and 2) until the nowcast time
- 4) Run HYCOM in forecast mode out to tau = 120

Approximate run times* (using 379 IBM Power 5+ processors):

- 1) Six NCODA analyses: 1.1 hrs/analysis = 6.6 hrs
- 2) Five HYCOM hindcast days @ 240 sec Δt : 0.8 hrs/day = 4.0 hrs
- 3) Five HYCOM forecast days @ 240 sec Δt : 0.8 hrs/day = 4.0 hrs
- 4) Total: 14.6 hrs

* Timings do not include PIPS coupling

MLD/SLD/BLG/DSC Evaluation

Mixed Layer Depth (MLD):
change in temperature of
.25°C from the surface

Sonic Layer Depth (SLD):
near surface sound speed
maximum

Below Layer Gradient (BLG):
fit a line to sound speed
points between SLD and
SLD + 100 m

Deep Sound Channel (DSC)
axis: deepest sound speed
minimum

